



RieberLok™ Gasket for Internal Restraint of AWWA C900 PVC Pipe & Fittings Originally Fitted with a Rieber Gasket



SUBMITTAL INFORMATION

PROJECT NAME:

ENGINEER:

CONTRACTOR:

SPEC. SECTION:

DATE:

INFORMATION:

- FM Approved
- Available in SBR or EPDM
- Stainless steel locking segments unaffected by corrosive elements
- Can be pre-installed at the plant or field installed
- Works on all C900 pipe & PVC pressure fittings that originally use a Rieber gasket
- Rated at the pipe or PVC pressure fitting rating with a 2:1 safety factor
- Allows the full deflection of the joint, as recommended by the pipe or fitting manufacturer
- Suitable for open trench, road bores, and casing applications. Please contact RieberLok for HDD applications
- Size range of 4" - 24" for C900 CIOD & 3" - 8" C900 IPS
- Works on C900 DR14, DR18, and DR25 for C900 CIOD & SDR17, SDR21, & SDR26
- Assembly instructions, field cut instructions, and FAQs on www.RieberLok.com

RieberLok Gasket Color Codes

For Rieber Gasket Replacement:		
1) CIOD, SBR	<input type="checkbox"/>	White
2) CIOD, EPDM	<input type="checkbox"/>	Orange
3) IPS, SBR	<input type="checkbox"/>	Pink
4) IPS, EPDM	<input type="checkbox"/>	Green



GASKET MATERIAL OPTIONS:

SBR

EPDM

